



Epson TM-T88VI-iHUB

Reliable, fast receipt printer with iHub connectivity, cloud and embedded server

Ultra fast and versatile printing up to 350 mm/s

Built-in web server for custom web applications

Use as a peripheral hub for mPOS solutions

Connect to multiple devices and cloud servers

Triple interfaces including built-in USB and Ethernet

Print from web-based apps with ePOS print technology

Industry leading four year warranty

Epson TM-T88VI-iHUB

Product Specifications

PAPER		GENERAL	
PAPER SIZE	80mm: 79.50 ± 0.50 (W) mm x dia 83.00 mm 58mm: 57.50 ± 0.50 (W) mm x dia 83.00 mm	PRODUCT DIMENSIONS	145 x 195 x 148 mm (Width x Depth x Height)
FONTS & STYLES		PRODUCT WEIGHT	1.6 kg
PRINT SPEED	350 mm/s	COLOUR	Black / White
PRINT SPEED (DEFAULT)	300 mm/s	INSTALLATION	Horizontally, wall hanging
PRINTING FONT	Font A (default): 12 x 24 Font B: 9 x 17 (including 2-dot horizontal spacing)	INTERFACE CONNECTORS	D.K.D. function
COLUMN CAPACITY RECEIPT	80mm: 42/48/56 columns 58mm: 30/36/40 columns	HUMIDITY	Operation 10% - 90%
CHARACTER SIZE	Font A: 1.41 x 3.39 (W x H mm) Font B: 0.99 x 2.40 (W x H mm)	TEMPERATURE	Operation 5° C - 45° C, Storage -10° C - 50° C
CHARACTER SET	95 Alphanumeric, 18 set International, 128 x 43 Graphic	STANDARD COMPLIANCE	
PRINTING CHARACTERS	Text (incl. Euro symbol), Graphics, Barcode	SAFETY APPROVALS	RCM: AS / NZS CISPR class A Energy-saving: ENERGY STAR
INTERFACES		OTHER	
CONNECTIVITY	Built-in USB, Built-in Ethernet (10/100Base-T/TX) +	WARRANTY	48 months
CONNECTION TYPE	USB type A connector x 1, USB type B connector x 4, RJ45 x 1, DB9 male x 1, DK x 1, 3 pin ,mini pin female x 1 Wireless (USB wireless dongle): OT-WL05 (802.11 a/b/g/n) or OT-WL02 (802.11 b/g/n) Beacon (using Bluetooth low energy): Beacon dongle (Epson approved dongle: Laird model BT-820)	WHAT'S IN THE BOX	
DATA BUFFER			Connector Cover Main unit PS-180 & AC cable Paper spacer Power switch cover Roll paper Setup guide Warranty document
DATA BUFFER	45 Bytes or 4 kb, selectable	OPTIONAL ACCESSORIES	
POWER		C32C845040	WH-10 (040) Wall hanging bracket
POWER SUPPLY	PS-180, AC cable	C32C890739	OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz
OPERATING VOLTAGE	24 V	C32C814596	Power supply cover
POWER CONSUMPTION	Operating: 27.6W Stand by: 0.5W	COVER PLUS (OPTION)	
		1YWT88VI-iHUB	CoverPlus1 yr service pack TM-T88VI-iHUB

Better Products for a Better Future



Bluetooth™



Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON AUSTRALIA
3 Talavera Road
North Ryde NSW 2113
Tel: (02) 8899 3666
www.epson.com.au
ABN 91 002 625 783

EPSON NEW ZEALAND
Level 2 7-9 Fanshawe Street
Auckland, 1010
Tel: 0800 443 478
www.epson.co.nz

06/17

Epson CoverPlus
Fast. Reliable. Professional

EPSON
EXCEED YOUR VISION